# Branched Schrödinger Bridge Matching

**Sophia Tang<sup>1</sup>**, Yinuo Zhang<sup>2</sup>, Alexander Tong<sup>3,4</sup>, Pranam Chatterjee<sup>1,5†</sup>

<sup>1</sup>Department of Computer and Information Science, University of Pennsylvania <sup>2</sup>Center of Computational Biology, Duke-NUS Medical School <sup>3</sup>Mila, Quebec AI Institute, <sup>4</sup>Université de Montréal <sup>5</sup>Department of Bioengineering, University of Pennsylvania <sup>†</sup>Correspondence to: pranam@seas.upenn.edu





# **Motivation**

enn


- 1. Schrödinger Bridge Matching Frameworks are Limited to Single Continuous Trajectories. Predicting how a population evolves between an initial and final state is central to many problems in generative modeling, from simulating perturbation responses to modeling cell fate decisions. Existing approaches, such as Flow Matching and Schrödinger Bridge Matching, effectively learn mappings between two distributions by modeling a single stochastic path but are restricted to modeling evolution along a single path.
- Branching Dynamics is Governed by Energy-Minimizing Trajectories. To define more complex systems where the optimal dynamics cannot be accurately captured by 2. minimizing the standard squared Euclidean cost in entropic OT, the Generalized Schrödinger Bridge (GSB) problem introduces an additional nonlinear state-cost.
- 3. Branching is Central to Modeling Cellular Perturbation Responses. When a homogeneous cell population undergoes a perturbation, such as gene knockouts or drug treatments, it frequently induces fate bifurcation as the cell population splits into multiple phenotypically distinct outcomes or commits to divergent cell fates

# Solving the Branched Generalized SB Problem with Conditional Stochastic Optimal Control (CondSOC)





### Multi-Path Navigation of 3D LiDAR Manifolds



#### Fig 2. Application of BranchSBM on Learning Branched Paths on a LiDAR Manifold. (Top) Plot of weight (left) and energy (right) evolution of each branch over time. (Bottom) Plots of the initial and target distributions, learned interpolants, and learned

branched trajectories on the LiDAR manifold.

### Modeling Cell Fate Differentiation




Fig 3. Application of BranchSBM on Modeling Differentiating Single-Cell Population Dynamics. Mouse hematopoiesis scRNA-seq data is provided for three time points. Simulated states (top) and trajectories (bottom) at time using single-branch SBM. Simulated states with BranchSBM at (B) t1 and (C) t2. (D) Learned trajectories on validation samples

### Modeling Drug-Induced Perturbation Responses




Fig 4. Comparison Between BranchSBM and Single-Branch SBM. Scaling BranchSBM across 50, 100, and 150 principal components and three branches outperforms single-branch SBM.

Fig 5. Results for Trametinib Perturbation Modeling with BranchSBM. (A) Clustered Trametinib perturbation data. (B) Three branches learned by BranchSBM. (C) Evolution of energy and mass.

### Conclusions

- 1. We define the Branched Generalized Schrödinger Bridge problem and introduce BranchSBM, a novel matching framework that learns optimal branched trajectories from an initial distribution to multiple target distributions.
- We derive the Branched Conditional Stochastic Optimal Control (CondSOC) problem as the sum of Unbalanced CondSOC objectives and 2. leverage a multi-stage training algorithm to learn the optimal branching drift and growth fields that transport mass along a branched trajectory
- We demonstrate the unique capability of BranchSBM to model dynamic branching trajectories while matching multiple target distributions across various problems, including 3D navigation over LiDAR manifolds, modeling differentiating single-cell population dynamics, and predicting heterogeneous cell states after perturbation.



Preprint